



ELECTRO-OPTICAL CHARACTERISTICS $T_A=25^\circ\text{C}$ PER CIRCUIT $I_f=60\text{mA} \times 2$				
PARAMETER	MIN	TYP	MAX	UNITS TEST COND
PEAK WAVELENGTH		574		nm
FORWARD VOLTAGE		4.2	4.5	V_f
REVERSE VOLTAGE	8			V_r $I_r=1\text{mA}$
LUMINOUS INTENSITY		35		cd/m^2 $I_f=50\text{mA} \times 2$
EMITTED COLOR:	GREEN			
REFLECTOR FINISH:	CLEAR WHITE WITH DIFFUSER			

LIMITS OF SAFE OPERATION AT 25°C PER CIRCUIT

PARAMETER	MAX	UNITS
STEADY CURRENT	80	mA
POWER DISSIPATION	0.36	W
DERATE FROM 25°C , PER DIE	-1.2	mW/ $^\circ\text{C}$
OPERATING, STORAGE TEMP.	-40 TO +85	$^\circ\text{C}$
SOLDERING TEMP.	+260	$^\circ\text{C}$
2.0mm FROM BODY		3 SEC. MAX



*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030), MIN=+DECIMAL PRECISION MAX.=+0.00 -DECIMAL PRECISION

REV.

PART NUMBER

SSB-CER6647SUGW

66mm x 47mm VIEW AREA, EDGE LIT LED BACKLIGHT
WITH REFLECTOR, 574nm GREEN, 10 CHIPS, 4.2V @ 50mA
PER CIRCUIT.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY:

JN

CHECKED BY:

APPROVED BY:

DATE: 5.31.07

PAGE: 1 OF 1

SCALE: N/A

Pb

UNCONTROLLED DOCUMENT