


UNCONTROLLED DOCUMENT

PART NUMBER
SSB-COB10018SRREV.
A

REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
A	E.C.N. #10BRDR. & REDRAWN.	1/19/00

ELECTRO-OPTICAL CHARACTERISTICS $T_A=25^\circ\text{C}$

PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		660 (RED)		nm	
FORWARD VOLTAGE		3.6	4.6	V_f	
REVERSE VOLTAGE	7			V_r	$V_r=100\mu\text{A}$
LUMINOUS INTENSITY		350		cd/m^2	$I_f=380\text{mA}$
EMITTED COLOR:	RED				
REFLECTOR FINISH:	CLEAR WHITE				

LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT	475	mA
STEADY CURRENT	380	mA
POWER DISSIPATION	2.5	W
DERATE FROM 25°C	62	$\text{mW}/^\circ\text{C}$
OPERATING TEMP.	-45 TO +85	$^\circ\text{C}$
STORAGE TEMP.	-45 TO +85	$^\circ\text{C}$
SOLDERING TEMP.	+230	$^\circ\text{C}$
2.0mm FROM BODY	5 SEC. MAX	

UNCONTROLLED DOCUMENT

*TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), LEAD LENGTH=±0.75 (±0.030), MIN=+0.00 DECIMAL PRECISION MAX=-0.00 DECIMAL PRECISION

REV.

A

PART NUMBER

SSB-COB10018SR

100mm x18mm BACKLIGHT DISPLAY, 38 CHIPS ON BOARD,
660nm SUPER RED CHIPS, MILKY WHITE DIFFUSER TAPE.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.

LUMEX
INCORPORATED

290 E. HELLEN ROAD
PALATINE, ILLINOIS 60067
PHONE: (847) 359-2790
WEB: <http://www.lumex.com>

DRAWN BY: CHECKED BY: APPROVED BY: DATE: 2-23-93

SS/DU

PAGE: 1 OF 1
SCALE: N/A