


UNCONTROLLED DOCUMENT



NOTES:

1. POSITIONS 1~5: YELLOW LEDs. (5 PCS.)
2. POSITIONS 8~11: RED LEDs. (4 PCS.)
3. POSITIONS 6, 7, 12, 13: WHITE LEDs. (4 PCS.)
4. NO LED IN POSITION 10.
5. OVERLAY: #LXP-0L4828.
6. REFLECTOR WITH 'LX' AND CAVITY NUMBER STAMPED.
7. PARTS TO BE PACKAGED IN ANTI-STATIC ENVIRONMENT.
8. SURFACE TEXTURE MOLDTECH# MT-11005 OR EQUIVALENT.

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN=+DECIMAL PRECISION MAX=+0.00 -0.00

PART NUMBER

SSB-DL4828SYSIUW-F

REV.

F

REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
A	E.C.N. #10718.	2.21.01
B	E.C.N. #10736.	5.7.01
C	E.C.N. #10785.	9.12.01
D	E.C.N. #10817.	12.5.01
E	E.C.N. #10833.	1.22.02
F	E.C.N. #11019.	7.16.03

ELECTRO-OPTICAL CHARACTERISTICS T _A =25°C PER LED I _f = 20 mA					
PARAMETER	YELLOW	WHITE	RED	UNITS	TEST COND
PEAK WAVELENGTH	590	550	636	nm	
FORWARD VOLTAGE (TYP.)	4.2	7.2	4.2	V _f	
FORWARD VOLTAGE (MAX.)	5.0	8.0	5.0	V _f	
REVERSE VOLTAGE	10.0	10.0	10.0	V _r	I _r =100μA
LUMINOUS INTENSITY	150	120	150	mcd	I _f =20mA
LED POSITION:	1~5	6,7,13,14	8,9,11,12		
REFLECTOR FINISH:	WHITE DIFFUSED				

LIMITS OF SAFE OPERATION AT 25°C PER CHIP

PARAMETER	COLORS	MAX	UNITS
PEAK FORWARD CURRENT*		150	mA
STEADY CURRENT		30	mA
POWER DISSIPATION	(R/Y/W)	100/105/105	mW
DERATE FROM 25°C		-0.25	mW/°C
OPERATING, STORAGE TEMP.		-40 TO +85	°C
SOLDERING TEMP.		+240	°C
2.0mm FROM BODY			3 SEC. MAX

* t<10μS

CAUTION: STATIC SENSITIVE DEVICE
FOLLOW PROPER E.S.D. HANDLING PROCEDURES
WHEN WORKING WITH THIS PART.

UNCONTROLLED DOCUMENT

REV.

F

PART NUMBER

SSB-DL4828SYSIUW-F

CUSTOM RED/YELLOW/WHITE BACKLIGHT,
CUSTOMER'S P/N: 601-00071 REV 10.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY:

CT

CHECKED BY:

APPROVED BY:

DATE: 12.27.00

PAGE: 1 OF 1

SCALE: N/A