



UNCONTROLLED DOCUMENT

PART NUMBER

SSD-LX011E565BGPU

REV.



ELECTRO-OPTICAL CHARACTERISTICS:

PARAMETER	SYMBOL	TEST COND	MIN	TYP	MAX	UNITS
FORWARD VOLTAGE	V_f	$I_f = 2\text{mA}$	1.75	1.90	2.25	V
REVERSE CURRENT	I_r	$V_r = 5\text{V}$			10	μA
PEAK WAVELENGTH	λ_p	$I_f = 2\text{mA}$		570		nm
SPECTRA HALF-WIDTH	$\Delta\lambda$	$I_f = 2\text{mA}$		30		nm
LUMINOUS INTENSITY	I_v	$I_f = 2\text{mA}$	0.2			mcd

NOTES:

1. UNITS: mil
2. GOLD METALIZATION.
3. P ELECTRODE UP ON TAPE.

UNCONTROLLED DOCUMENT

REV.

PART NUMBER

SSD-LX011E565BGPU

GaP GREEN LED CHIP.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY:

CHECKED BY:

APPROVED BY:

DATE: 6.4.01

TM/BC

PAGE: 1 OF 1

SCALE: N/A