

UNCONTROLLED DOCUMENT


SC:0.50

PART NUMBER

SSD-LX78-7

REV.

P4



PRELIMINARY IN P/N DIR

NOTES:

- SSD-LX014E675DGPU (30 PCS.) CHIPS:1,5,...57
- SSD-LX010E1550CGPU (30 PCS) CHIPS:2,4,6,8,...80
- SSD-LX008E475CGPNU (9 PCS) CHIPS:61-78
- LXP-PCBCER78
- FR4 RESISTOR BOARD
- LED COATED BY NORLAND NOA 68.
- TOLERANCE FOR CHIPS $\pm 10\text{nm}$ & $\pm 5\%$ POWER OUTPUT.
- THERMISTOR, $2.5\text{k}\Omega$ @ ROOM TEMP, 0805 PACKAGE (3 PCS.)
- SAMTEC #BBS-116-G-A, SYMBOL:
- GOLD PLATED INTERCONNECT PINS (48 PCS.), SYMBOL:
- 620Ω RESISTOR, 1% 0805 PACKAGE (39 PCS.)
- 7.5Ω HEATER ON BOTTOM OF CERAMIC BOARD.
- $1\mu\text{F}$ CAPACITOR, 0805 PACKAGE (7 PCS.)
- RESISTORS & CAPACITOR NOT SHOWN.
- 489826-7, MM/YY-LX TO BE MARKED ON PCB, WHERE MM/YY IS MONTH/YEAR OF MANUFACTURE.
- PACKAGE PARTS IN PINK ANTISTATIC TRAYS.

ELECTRO-OPTICAL CHARACTERISTICS:

PARAMETER	SYMBOL	TEST COND	675nm	475nm	1550nm	UNITS
FORWARD VOLTAGE TYP.	V_f	$I_f=20\text{mA}$	1.8	3.2	0.8	V
FORWARD VOLTAGE MAX.	V_f	$I_f=20\text{mA}$	2.2	3.4	1.3	V
MAX REVERSE CURRENT	I_r	$V_r=3\text{V}$	10	10	10	μA
PEAK WAVELENGTH	λ_p	$I_f=20\text{mA}$	675	475	1550	nm
SPECTRA HALF-WIDTH	$\Delta\lambda$	$I_f=20\text{mA}$	20	50	50	nm
POWER INTENSITY	I_v	$I_f=20\text{mA}$	2.0	5.0	0.4	mW

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030), MIN.=+0.00/-0.00

REV.

P4

PART NUMBER

SSD-LX78-7

CUSTOM IR CERAMIC BOARD,

9:475nm, 30:1550nm, 30:675nm.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY:

JN

CHECKED BY:


APPROVED BY:

DATE: 05.07.08

PAGE: 1 OF 2

SCALE: N/A

PRELIMINARY IN P/N DIR



EPOXY NOTES:

1. EPOXY TO BE FREE OF BUBLES AND FOREIGN OBJECTS.
2. THE EPOXY SURFACE WILL BE UNIFORM AND FREE OF SCRATCHES.
3. AFTER CURING, THE EPOXY WILL NOT BE TACKY AND MUST BE STRONG ENOUGH TO NOT DAMAGE DURING NORMAL HANDLING.
4. THE PCB WILL BE FREE OF EPOXY, ESPECIALLY IN THE VICINITY OF MOUNTING HOLES.

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +DECIMAL PRECISION -0.00 MAX.= +0.00 -DECIMAL PRECISION

REV.

P4

PART NUMBER

SSD-LX78-7

CUSTOM IR CERAMIC BOARD,
30:675nm, 30:1550nm, 9:470nm.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY:

JIN

CHECKED BY:

APPROVED BY:

DATE: 05.07.08

PAGE: 2 OF 2

SCALE: N/A