


DATE	REVISIONS	REV
8-15-94	CHG'D. OPER/STOR. TEMPS AND STAND-OFF/	A
3-6-95	CHG'D. STANDOFF, UPDATED SPECS./	B
9-23-96	E.C.N. #10244./	C

DRAWING NUMBER
SSF-LXH340GGYD

REV
C



ELECTRO-OPTICAL CHARACTERISTICS TA=25 °C If=20mA

PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH	POS. 1	565 (GREEN)		nm	
	POS. 2	565 (GREEN)		nm	
	POS. 3	585 (YELLOW)		nm	
FORWARD VOLTAGE		2.1	2.8	V _f	
REVERSE VOLTAGE	5.0			V _r	I _r =100uA
AXIAL INTENSITY		15		mcd	I _f =20mA
VIEWING ANGLE		80		2x theta	
EMITTED COLOR:	POS. 1-GRN	POS. 2-GRN	POS. 3-YEL		
EPOXY LENS FINISH:	YELLOW, GREEN DIFFUSED				

② LIMITS OF SAFE OPERATION AT 25 DEG. C

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT *	150	mA
STEADY CURRENT(G/Y)	25/30	mA
POWER DISSIPATION	105	mW
DERATE FROM 25 °C	-1.6	mW/ °C
① OPERATING, STORAGE TEMP.	-40 TO +85	°C
① LEAD SOLDERING TEMP.	+260	°C
① 2.0mm FROM BODY	3 SEC. MAX	

* t<10uS

BILL OF MATERIALS:

- SSH-LXH340 HOLDER. MATERIAL: BLACK NYLON 94V-0.
- SSL-LX3044GD LED.
- SSL-LX3044GD LED.
- SSL-LX3044YD LED.

RELIABILITY NOTE:

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.

LUMEX
OPTO COMPONENTS INC.

290 E. HELLEN ROAD
PALATINE, ILLINOIS 60067
(847) 359-2790

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX OPTO/COMPONENTS, INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX OPTO/COMPONENTS, INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

DATE: 12-21-93	DWN:	CHK'D:	APPD:
SCALE: N/A			

T-3mm LED, RIGHT ANGLE FAULT INDICATOR,
GREEN/GREEN/YELLOW DIFFUSED

PAGE 1 OF 1	DRAWING NUMBER SSF-LXH340GGYD	REV C
-------------	----------------------------------	----------