


PART NUMBER	SSI-LXH072IGW-WH	REV.	D
DATE	E.C.N. NUMBER AND REVISION COMMENTS		REV.
12.20.94	UPDATED SAFE OPERATING SPECS.		A
01.05.99	E.C.N. #10BRDR. & REDRAWN.		B
01.10.01	E.C.N. #10702.		C
04.11.11	E.C.N. #10BRDR. & REDRAWN/#11686.		D

ELECTRO-OPTICAL CHARACTERISTICS $T_A=25^{\circ}\text{C}$ $I_f=20\text{mA}$					
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH (R/G)		635/565		nm	
FORWARD VOLTAGE (R/G)		2.0/2.2	2.5/2.6	V_f	
REVERSE VOLTAGE	5.0			V_r	$I_f=100\mu\text{A}$
AXIAL INTENSITY (R/G)		15/9		mcd	$I_f=20\text{mA}$
VIEWING ANGLE		110		2θ	
EMITTED COLOR:	RED/GREEN				
EPOXY LENS FINISH:	MILKY WHITE DIFFUSED				

A LIMITS OF SAFE OPERATION AT 25°C		
PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	150	mA
STEADY CURRENT (R/G)	30/25	mA
POWER DISSIPATION	105	mW
DERATE FROM 25°C	-1.2	mW/°C
OPERATING TEMP.	-40 TO +85	°C
STORAGE TEMP.	-40 TO +85	°C
SOLDERING TEMP.	+260	°C
2.0mm FROM BODY	3	SEC. MAX

* $t < 10\mu\text{s}$

NOTES:

- 1. SSH-LXH072WH HOLDER, OFF WHITE.
- 2. SSL-LX25783IGW LED, RED/GREEN BICOLOR.
- 3. SECURE LED TO HOLDER WITH GLUE.
- 4. PANEL CUT OUT SIZE: 5.3mm x 11.0mm.