





| PART NUMBER | SSL-LX3054YT/R                      | REV. | B    |
|-------------|-------------------------------------|------|------|
| DATE        | E.C.N. NUMBER AND REVISION COMMENTS |      | REV. |
| 04.09.01    | E.C.N. #10BRDR. & REDRAWN IN 3D.    |      | A    |
| 09.17.12    | E.C.N. #10BRDR. & REDRAWN.          |      | B    |



| ELECTRO-OPTICAL CHARACTERISTICS Ta=25°C If=20mA |                    |     |     |          |           |
|-------------------------------------------------|--------------------|-----|-----|----------|-----------|
| PARAMETER                                       | MIN                | TYP | MAX | UNITS    | TEST COND |
| PEAK WAVELENGTH                                 |                    | 585 |     | nm       |           |
| FORWARD VOLTAGE                                 |                    | 2.1 | 2.5 | Vf       |           |
| REVERSE VOLTAGE                                 | 5.0                |     |     | Vr       | If=100µA  |
| AXIAL INTENSITY                                 |                    | 90  |     | mcd      | If=20mA   |
| VIEWING ANGLE                                   |                    | 30  |     | 2x theta |           |
| EMITTED COLOR:                                  | YELLOW             |     |     |          |           |
| LENS FINISH:                                    | YELLOW TRANSPARENT |     |     |          |           |

| LIMITS OF SAFE OPERATION AT 25°C |            |       |
|----------------------------------|------------|-------|
| PARAMETER                        | MAX        | UNITS |
| PEAK FORWARD CURRENT*            | 150        | mA    |
| STEADY CURRENT                   | 30         | mA    |
| POWER DISSIPATION                | 105        | mW    |
| DERATE FROM 25°C                 | -1.6       | mW/°C |
| OPERATING TEMP.                  | -40 TO +85 | °C    |
| STORAGE TEMP.                    | -40 TO +85 | °C    |
| SOLDERING TEMP.                  | +260       | °C    |
| 2.0mm FROM BODY                  | 3          | SEC.  |

\* t&lt;10µs

\*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN.= <sup>+DECIMAL PRECISION</sup><sub>-0.00</sub> MAX.= <sup>+0.00</sup><sub>-DECIMAL PRECISION</sub>

UNCONTROLLED DOCUMENT