



| PART NUMBER | SSL-LX5093SBT/A                     | REV. | C    |
|-------------|-------------------------------------|------|------|
| DATE        | E.C.N. NUMBER AND REVISION COMMENTS |      | REV. |
| 05.31.01    | E.C.N. #10BRDR. & REDRAWN.          |      | A    |
| 10.23.06    | E.C.N. #11148.                      |      | B    |
| 09.04.12    | E.C.N. #10BRDR. & REDRAWN.          |      | C    |



| ELECTRO-OPTICAL CHARACTERISTICS Ta=25°C If=20mA |                  |     |     |          |           |
|-------------------------------------------------|------------------|-----|-----|----------|-----------|
| PARAMETER                                       | MIN              | TYP | MAX | UNITS    | TEST COND |
| PEAK WAVELENGTH                                 |                  | 430 |     | nm       |           |
| FORWARD VOLTAGE                                 |                  | 4.5 | 5.5 | Vf       |           |
| REVERSE VOLTAGE                                 | 5.0              |     |     | Vr       | If=100μA  |
| AXIAL INTENSITY                                 |                  | 100 |     | mcd      | If=20mA   |
| VIEWING ANGLE                                   |                  | 30  |     | 2x theta |           |
| EMITTED COLOR:                                  | BLUE             |     |     |          |           |
| EPOXY LENS FINISH:                              | BLUE TRANSPARENT |     |     |          |           |

## LIMITS OF SAFE OPERATION AT 25°C

| PARAMETER             | MAX        | UNITS |
|-----------------------|------------|-------|
| PEAK FORWARD CURRENT* | 100        | mA    |
| STEADY CURRENT        | 30         | mA    |
| POWER DISSIPATION     | 98         | mW    |
| DERATE FROM 25°C      | -1.0       | mW/°C |
| OPERATING TEMP.       | -40 TO +85 | °C    |
| STORAGE TEMP.         | -40 TO +85 | °C    |
| SOLDERING TEMP.       | +260       | °C    |
| 2.0mm FROM BODY       | 3          | SEC.  |

\* t&lt;10μs

CAUTION: STATIC SENSITIVE DEVICE  
FOLLOW PROPER E.S.D. HANDLING PROCEDURES  
WHEN WORKING WITH THIS PART.

\*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN.= +DECIMAL PRECISION MAX.= +DECIMAL PRECISION -0.00 -DECIMAL PRECISION

UNCONTROLLED DOCUMENT

QUASARBRITE T-5mm (T-1 3/4) 430nm BLUE LED, BLUE TRANSPARENT LENS.

\*\*THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.\*\*

CONFIDENTIAL INFORMATION  
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL  
KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

|        |           |           |    |
|--------|-----------|-----------|----|
| DATE:  | 09.04.12  | DRAWN BY: | AB |
| PAGE:  | 1 OF 1    | CHKD BY:  | KF |
| SCALE: | NTS       | APRVD BY: | KF |
| UNIT:  | mm [INCH] |           | Ⓟ  |