UNCONTROLLED DOCUMENT


CAUTION: STATIC SENSITIVE DEVICE FOLLOW PROPER E.S.D. HANDLING PROCEDURES WHEN WORKING WITH THIS PART.

PART NUMBER
SSL-LX5093USBDBLA4


E.C.N. NUMBER AND REVISION COMMENTS DATE E.C.N. #11148 10.30.06


REV.

ø5.90	[ø0.232] —	_	ø5.00	[ø0.197]
		+		
	/			



PARAMETER MIN TYP MAX UNITS TEST COND PEAK WAVELENGTH 470 nm FORWARD VOLTAGE 3.5 4.0 Vf REVERSE VOLTAGE 5.0 Vr I _T =100μA AXIAL INTENSITY 300 mcd I _f =20mA VIEWING ANGLE 60 2x theta EMITTED COLOR: EMITTED COLOR: BLUE EPOXY LENS FINISH: BLUE DIFFUSED	ELECTRO-OPTICAL CH	ARACTERIS	STICS TA=25°0	3	If=20mA	
FORWARD VOLTAGE 3.5 4.0 Vf REVERSE VOLTAGE 5.0 Vr Ir=100µA AXIAL INTENSITY 300 mcd If=20mA VIEWING ANGLE 60 2x theta EMITTED COLOR: BLUE	PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
REVERSE VOLTAGE 5.0 V_r I_r =100 μ A AXIAL INTENSITY 300 mcd I_f =20mA VIEWING ANGLE 60 2x theta EMITTED COLOR:	PEAK WAVELENGTH		470		nm	
AXIAL INTENSITY 300 mcd I_f = 20mA VIEWING ANGLE 60 2x theta EMITTED COLOR: BLUE	FORWARD VOLTAGE		3.5	4.0	V_f	
VIEWING ANGLE 60 2x theta EMITTED COLOR: BLUE	reverse voltage	5.0			V_{Γ}	I _r =100μΑ
EMITTED COLOR: BLUE	AXIAL INTENSITY		300		mcd	I _f = 20mA
	VIEWING ANGLE		60		2x theta	
EPOXY LENS FINISH: BLUE DIFFUSED	EMITTED COLOR:	BLUE				
	EPOXY LENS FINISH:	BLUE DI	FFUSED			





LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	100	mA
STEADY CURRENT	30	mA
POWER DISSIPATION	105	тW
DERATE FROM 25°C	- 1.2	mW∕°C
OPERATING, STORAGE TEMP.	- 40 TO +85	*C
SOLDERING TEMP.	+ 260	" C
2,0mm FROM BODY		3 SEC. MAX

* t<10µS



UNCONTROLLED DOC

*UNILESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MN= +0.001

REV.

PART NUMBER SSL-LX5093USBDBLA4

T-5mm (T-1 3/4) 470nm ULTRA SUPER BLUE LED, CUSTOM LEAD BEND, BLUE DIFFUSED LENS.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY DF
LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX
INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 US WEB: www.lumex.com TW WEB: www.lumex.com.tw

DRAWN BY: CHECKED BY: APPROVED BY: DATE: 10.30.06 PAGE: 1 OF 1 SCALE: N/A JC